

Application No.: 09/777,849
Inventor: BRÖCKER et al.
Amendment of November 9, 2005
Reply to Office Action of August 11, 2005
Docket No.: 51157

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (canceled)
2. (canceled)
3. (currently amended) A process for the production of catalyst packing for a reactor having one or more course(s) that completely fill the reactor cross section, the catalyst packing comprising a plurality of stacked layers of fabricated woven or knitted fabric in the form of continuous web goods, wherein the layers are arranged perpendicular to the principal flow direction in the reactor, and a course is formed from at least three segments (S), the process as claimed in claim 1, wherein in which a fabricated woven or knitted fabric in the form of continuous web goods is shaped to give a package by stacking a plurality of layers thereof one on top of the other, which comprises cutting segments (S) out of the package and assembling them to give one or more course(s) which completely fill the reactor cross section.
4. (original) A process as claimed in claim 3, wherein respective stacked layers in a package are rotated by 180° to one another.
5. (previously presented) A process as claimed in claim 3, wherein the following sequence of cuts is used to separate the segments (S) from the package:
 - a) a first segment (S) with a length equal to twice the reactor radius or a first pair of segments with a length equal to the reactor radius for placing in the center of the reactor cross section is removed by rectangular cuts,
 - b) two further pairs of segments each with length $2 \cdot l_1$, where

$$l_1 = \sqrt{r^2 - x^2}$$

Application No.: 09/777,849
Inventor: BRÖCKER et al.
Amendment of November 9, 2005
Reply to Office Action of August 11, 2005
Docket No.: 51157

BEST AVAILABLE COPY

- where r = reactor internal radius and x = web width of the package,
are removed by rectangular cuts and are subsequently divided into in each case two
geometrically identical segments (S) by an inclined cut along the tangents at the
reactor interior circle at a point T_1 which is at a distance x from the longitudinal axis
of the first segment (S), for placing on both sides of the first, central segment (S), and
c) optionally further pairs of segments are removed, in each case in double the number
corresponding to the cut sequence in b), with a length $2 \cdot l_i$, where i = natural number,
 $i \geq 2$, where

$$l_i = \sqrt{r^2 - i \cdot x^2}$$

- and where the point T_i at which the tangent to the reactor interior circle is placed is in
each case at a distance of i times x from the longitudinal axis of the first, central
segment (S), and
d) in order to fill the two edge gaps, segments (S) are removed from the package
analogously to a), b) and c), but for insertion rotated by an angle of 90° to the
segments (S) already inserted.
6. (previously presented) A process as claimed in claim 3, wherein continuous web goods having
a width of from 50 to 500 mm are employed.
 7. (previously presented) A process as claimed in claim 3, wherein a package having a thickness
of from 40 to 400 mm is produced by stacking the continuous web goods.
 8. (previously presented) A process as claimed in claim 3, wherein one or more grille(s) is (are)
arranged in the reactor for accommodating the course(s).
 9. (previously presented) A process as claimed in claim 8, wherein from 1 to 6 course(s) is (are)
arranged on a grille.
 10. (previously presented) A process as claimed in claim 3, wherein the segments (S) arranged
one on top of the other in the reactor longitudinal direction in two successive courses are in
each case arranged rotated with respect to one another.

Application No.: 09/777,849
Inventor: BRÖCKER et al.
Amendment of November 9, 2005
Reply to Office Action of August 11, 2005
Docket No.: 51157

BEST AVAILABLE COPY

11. (previously presented) A method of conducting a catalytic reaction which comprises providing the catalyst packing produced as claimed in claim 3 and arranging the catalyst packing in a reactor for catalytic reactions.
12. (previously presented) A process as claimed in claim 6, wherein the width of the continuous web goods is from 100 to 300 mm.
13. (previously presented) A process as claimed in claim 7, wherein the thickness of the package is from 100 to 250 mm.
14. (previously presented) A process as claimed in claim 8, wherein the grilles are connected to one another and/or to the reactor internal wall.
15. (previously presented) A process as claimed in claim 9, wherein from 2 to 4 courses are arranged on a grille.
16. (previously presented) A process as claimed in claim 10, wherein the segments (S) are in each case arranged rotated with respect to one another by an angle of 45°.
17. (previously presented) The method of claim 11, wherein the catalytic reaction is a hydrogenation, a selective hydrogenation, a selective oxidation or an isomerization reaction.
18. (new) The process of claim 3 wherein segments (S) adjacent to one another in each case at their rectangular faces are arranged symmetrically to one another with respect to the rectangular face.